



QSCControl.net, QSC’s next generation network audio system, achieves the seamless integration of the company’s signal transport, control, processing, and monitoring technologies. QSCControl.net brings together QSC’s digital, power amplification and loudspeaker products into a unified system that enables the user to administrate it all via a fully integrated graphical user interface. The new generation BASIS devices are designed to operate under the company’s QSCControl.net platform.

**BASIS 902zz**

The BASIS platform meets the control, monitoring, signal transport and processing needs of amplification and loudspeaker systems over an Ethernet network. The BASIS 902zz units combine three distinct QSC technologies within a single hardware unit. Amplifier and loudspeaker control, monitoring and protection, configurable DSP, and CobraNet™ audio transport are seamlessly integrated into one powerful single RU package.

Through QSCControl.net, QSC’s BASIS and next-generation RAVE and DSP products can be networked together and controlled from a single software interface. In addition, multiple networked computers can be set up to control and monitor all of the units simultaneously.

**Fixed Latency DSP**

Users of most other configurable DSP systems are familiar with a variable latency inherent in the processing configuration. Add more processing blocks and you also add delay, whether you want it or not. QSC’s DSP engine is unique in having a short and fixed processing latency through the DSP subsystem. QSC’s fixed latency DSP is configurable DSP that stays fast and predictable from one configuration to the next.

For more information, visit [www.qscontrol.net](http://www.qscontrol.net)

*CobraNet is a trademark of Cirrus Logic, Inc.  
 THX is a trademark of THX Ltd.*

| Inputs   | DSP     | Outputs                |
|----------|---------|------------------------|
| CobraNet |         | DataPort      CobraNet |
| 24 of 32 | 24 x 24 | 4(8 channels)      32  |

**Features**

- Amplifier and loudspeaker control, monitoring and protection
- Configurable DSP functions and signal paths
- Fixed latency DSP engine
- Ethernet controllable
- CobraNet audio transport with new intuitive GUI
- Two Ethernet ports – CobraNet and control can be run over a single cable or be divided between the two ports. The CobraNet port is 100Base-T. The control port is 10Base-T
- Each unit can store eight design configurations that can be changed on the fly
- Snapshots can recall config or block and/or parameter settings
- THX™ approved for professional cinema applications

**DSP functions include, but are not limited to:**

- Matrix mixer – any size, up to 24 x 24
- Automixers – gain sharing
- Routers – any size, up to 24 x 24
- Gain controls – any channel count, up to 24
- Graphic equalizers
- Filters – high-pass, low-pass, all-pass, shelf, parametric, parametric shelf, Butterworth high and low-pass, Linkwitz-Riley high and low-pass, Bessel-Thomson high and low-pass
- Crossovers – Linkwitz-Riley, Butterworth, Bessel-Thomson in-phase, Bessel-Thomson symmetrical, 2-way, 3-way, and 4-way general purpose adjustable
- Compressors, peak limiters, AGC’s, gates, dynamics processor
- Duckers – up to 8 channels, up to 60 seconds fade in and fade out times, priority mix
- Pink noise, white noise, sine generators
- Delays
- Macros – user-definable custom blocks with password protection

## PERFORMANCE

### Dynamic Range (AES-17, -60 dB method, all sensitivities)

|            |          |
|------------|----------|
| Unweighted | > 112 dB |
| A weighted | > 115 dB |

### Distortion (20 Hz – 20 kHz, all sensitivities)

|                           |                |
|---------------------------|----------------|
| +4 dBu (maximum)          | < 0.009% THD+N |
| 2 dB below clip (maximum) | < 0.009% THD+N |

### Crosstalk (20 Hz – 20 kHz)

|                         |          |
|-------------------------|----------|
| Inter-channel (maximum) | > 75 dB  |
| Inter-channel (typical) | > 90 dB  |
| Intra-channel (maximum) | > 85 dB  |
| Intra-channel (typical) | > 100 dB |

### Frequency Response

|                          |            |
|--------------------------|------------|
| 20 Hz – 20 kHz (maximum) | +/- 0.5 dB |
| 20 Hz – 20 kHz (typical) | +/- 0.2 dB |

### Audio Converters

24 bit, 48 kHz (output)

### Mute

Infinite attenuation

### Delay

|                                   |                    |
|-----------------------------------|--------------------|
| <b>Standard CobraNet™ latency</b> | <b>Low latency</b> |
| 6.313 milliseconds                | 3.646 milliseconds |

Network to BASIS

*CobraNet input through full DSP chain to analog output*

## INPUTS/OUTPUTS

### Program Outputs

|                           |   |
|---------------------------|---|
| 8 outputs                 |   |
| Connector Type            | 4 HD-15 DataPort connections  |
| Cable Type                | QSC DataPort cable, QSC p-n DPC-x ("x" designates cable length in feet)               |
| Available "Stock" Lengths | 1, 2, 3, 4, 5, 6, 10, and 20 ft, custom lengths available                             |
| Maximum Qualified Length  | 328 ft. (100 m) using QSC DP cable only / Non QSC cable limited to 6 ft. (audio only) |

## MONITOR

### Control Room Foldback Monitoring

|                |   |
|----------------|---|
| Connector type | 5-pin "phoenix style" (a.k.a. "euro style") detachable terminal blocks                          |
| Pinout         | 1:-(input) / 2:-(input) / 3:CHASSIS GND / 4:-(output) / 5:+(output)                             |
| Tap Points     | 8 internal input / 8 internal output / 8 amplifier (pre-, post-, amplifier) software selectable |

### Monitor Input

|                           |                                     |
|---------------------------|-------------------------------------|
| Monitor Signal (unit off) | Unity gain connection, relay bypass |
| Maximum Level             | +21 dBu                             |
| Impedance (nominal)       | 10k ohms                            |
| CMRR, 20 Hz – 20 kHz      | > 54 dB                             |

### Monitor Output

|                                     |  |
|-------------------------------------|--|
| Monitor                             | Sum of monitor input and signal from internal monitor tap point(s) |
| Frequency Response (20 Hz – 20 kHz) | +/- 0.5 dB   |
| Distortion (20 Hz – 20 kHz)         | < 0.05% at +4 dBu  |
| Noise Floor                         | > 90 dB  |
| Output Impedance (nominal)          | 100Ω   |
| Output Load (minimum)               | 600Ω   |

### Monitor Level

|                         |                                  |
|-------------------------|----------------------------------|
| Control Range (nominal) | 0 dB to -95.5 dB in 0.5 dB steps |
|-------------------------|----------------------------------|

## CONTROL INPUTS/OUTPUTS

### Relay Outputs

|  |  |
|--|--|
| 2 discrete floating relay switch outputs |  |
| Connector Type                           | 3-pin "phoenix style" (a.k.a. "euro style") detachable terminal blocks |
| Configuration                            | Electromechanical relay  |
| Pinout                                   | 1:NC / 2:NO / 3:COM  |
| Switching Capacity (nominal)             | 1A 30 VDC  |

### Logic Outputs

|                    |  |
|--------------------|--|
| 4 discrete outputs |  |
| Connector Type     | 2-pin "phoenix style" (a.k.a. "euro style") detachable terminal blocks |
| Configuration      | Single-ended, TTL compatible   |
| Pinout             | 1:+(Signal) / 2:-(CHASSIS GND)   |

### Omni Inputs

|  |  |
|--|--|
| 6 discrete inputs for TTL logic, voltage control or passive resistance |  |
| Connector Type   | 2-pin "phoenix style" (a.k.a. "euro style") detachable terminal blocks |
| Configuration  | Single-ended, ground referenced  |
| Pinout   | 1:+(Signal) / 2:-(CHASSIS GND)   |
| Normal Operating Range   | Reads signals between 0-5 V nominally                                  |
| Potentiometer Operation  | Use 10k ohms for full range  |
| Voltage Tolerance  | +/- 48 V   |
| Current Output   | 0.5 mA with 10k pot (for passive resistive controls)                   |

### RS-232 Port

Female DB9 connector (setup and diagnostics only)

### QSCControl Port

Neutrik Ethercon RJ45 ruggedized data connector

### CobraNet Port

Neutrik Ethercon RJ45 ruggedized data connector

## Indicators

|                        |   |
|------------------------|---|
| QSCControl Status      | Yellow Link, Tx, Rx, front panel / Green Link, Tx, Rx, rear panel |
| CobraNet Status        | Yellow Link, Tx, Rx, front and rear panel                         |
| Power                  | Blue, front panel   |
| Diagnostic             | Red, front panel  |
| DataPort Status (port) | Tri-state (red, green, yellow), front panel                       |
| LCD Data Display       | 2 line x 16 character, backlit, front panel                       |

Specifications subject to change without notice.

1675 MacArthur Boulevard • Costa Mesa, CA 92626 • Ph: 800/854-4079 or 714/957-7100 • Fax: 714/754-6174

BASIS 902zz - 04/23/07