



QSCControl.net, QSC’s next generation network audio system, achieves the seamless integration of the company’s signal transport, control, processing, and monitoring technologies. QSCControl.net brings together QSC’s digital, power amplification and loudspeaker products into a unified system that enables the user to administrate it all via a fully integrated graphical user interface. The new generation BASIS devices are designed to operate under the company’s QSCControl.net platform.

BASIS 904zz

The BASIS platform meets the control, monitoring, signal transport and processing needs of amplification and loudspeaker systems over an Ethernet network. The BASIS 904zz units combine three distinct QSC technologies within a single hardware unit. Amplifier and loudspeaker control, monitoring and protection, configurable DSP, and CobraNet™ audio transport are seamlessly integrated into one powerful single RU package.

Through QSCControl.net, QSC’s BASIS and next-generation RAVE and DSP products can be networked together and controlled from a single software interface. In addition, multiple networked computers can be set up to control and monitor all of the units simultaneously.

Fixed Latency DSP

Users of most other configurable DSP systems are familiar with a variable latency inherent in the processing configuration. Add more processing blocks and you also add delay, whether you want it or not. QSC’s DSP engine is unique in having a short and fixed processing latency through the DSP subsystem. QSC’s fixed latency DSP is configurable DSP that stays fast and predictable from one configuration to the next.

For more information, visit www.qscontrol.net

*CobraNet is a trademark of Cirrus Logic, Inc.
 THX is a trademark of THX Ltd.*

Inputs	DSP	Outputs
CobraNet		DataPort CobraNet
24 of 32	24 x 24	8(16 channels) 32

Features

- Amplifier and loudspeaker control, monitoring and protection
- Configurable DSP functions and signal paths
- Fixed latency DSP engine
- Ethernet controllable
- CobraNet audio transport with new intuitive GUI
- Two Ethernet ports – CobraNet and control can be run over a single cable or be divided between the two ports. The CobraNet port is 100Base-T. The control port is 10Base-T
- Each unit can store eight design configurations that can be changed on the fly
- Snapshots can recall config or block and/or parameter settings
- THX™ approved for professional cinema applications

DSP functions include, but are not limited to:

- Matrix mixer – any size, up to 24 x 24
- Automixers – gain sharing
- Routers – any size, up to 24 x 24
- Gain controls – any channel count, up to 24
- Graphic equalizers
- Filters – high-pass, low-pass, all-pass, shelf, parametric, parametric shelf, Butterworth high and low-pass, Linkwitz-Riley high and low-pass, Bessel-Thomson high and low-pass
- Crossovers – Linkwitz-Riley, Butterworth, Bessel-Thomson in-phase, Bessel-Thomson symmetrical, 2-way, 3-way, and 4-way general purpose adjustable
- Compressors, peak limiters, AGC’s, gates, dynamics processor
- Duckers – up to 8 channels, up to 60 seconds fade in and fade out times, priority mix
- Pink noise, white noise, sine generators
- Delays
- Macros – user-definable custom blocks with password protection

PERFORMANCE

Dynamic Range (AES-17, -60 dB method, all sensitivities)

Unweighted	> 112 dB
A weighted	> 115 dB

Distortion (20 Hz – 20 kHz, all sensitivities)

+4 dBu (maximum)	< 0.009% THD+N
2 dB below clip (maximum)	< 0.009% THD+N

Crosstalk (20 Hz – 20 kHz)

Inter-channel (maximum)	> 75 dB
Inter-channel (typical)	> 90 dB
Intra-channel (maximum)	> 85 dB
Intra-channel (typical)	> 100 dB

Frequency Response

20 Hz – 20 kHz (maximum)	+/- 0.5 dB
20 Hz – 20 kHz (typical)	+/- 0.2 dB

Audio Converters

24 bit, 48 kHz (output)

Mute

Infinite attenuation

Delay

Standard CobraNet™ latency	Low latency
6.313 milliseconds	3.646 milliseconds

Network to BASIS
CobraNet input through full DSP chain to analog output

INPUTS/OUTPUTS

Program Outputs

Connector Type	16 outputs
Cable Type	8 HD-15 DataPort connections
Available "Stock" Lengths	QSC DataPort cable, QSC p-n DPC-x ("x" designates cable length in feet)
Maximum Qualified Length	1, 2, 3, 4, 5, 6, 10, and 20 ft., custom lengths available
	328 ft. (100 m) using QSC DP cable only / Non QSC cable limited to 6 ft. (audio only)

MONITOR

Control Room Foldback Monitoring

Connector type	5-pin "phoenix style" (a.k.a. "euro style") detachable terminal blocks
Pinout	1:+(input) / 2:-(input) / 3:CHASSIS GND / 4:-(output) / 5:+(output)
Tap Points	8 internal input / 8 internal output / 8 amplifier (pre-, post-, amplifier) software selectable

Monitor Input

Monitor Signal (unit off)	Unity gain connection, relay bypass
Maximum Level	+21 dBu
Impedance (nominal)	10k ohms
CMRR, 20 Hz – 20 kHz	> 54 dB

Monitor Output

Monitor	Sum of monitor input and signal from internal monitor tap point(s)
Frequency Response (20 Hz – 20 kHz)	+/- 0.5 dB
Distortion (20 Hz – 20 kHz)	< 0.05% at +4 dBu
Noise Floor	> 90 dB
Output Impedance (nominal)	100Ω
Output Load (minimum)	600Ω

Monitor Level

Control Range (nominal)	0 dB to -95.5 dB in 0.5 dB steps
-------------------------	----------------------------------

CONTROL INPUTS/OUTPUTS

Relay Outputs

Connector Type	2 discrete floating relay switch outputs
Configuration	3-pin "phoenix style" (a.k.a. "euro style") detachable terminal blocks
Pinout	Electromechanical relay
Switching Capacity (nominal)	1:NC / 2:NO / 3:COM 1A 30 VDC

Logic Outputs

Connector Type	4 discrete outputs
Configuration	2-pin "phoenix style" (a.k.a. "euro style") detachable terminal blocks
Pinout	Single-ended, TTL compatible 1:+(Signal) / 2:-(CHASSIS GND)

Omni Inputs

Connector Type	6 discrete inputs for TTL logic, voltage control or passive resistance
Configuration	2-pin "phoenix style" (a.k.a. "euro style") detachable terminal blocks
Pinout	Single-ended, ground referenced 1:+(Signal) / 2:-(CHASSIS GND)
Normal Operating Range	Reads signals between 0-5 V nominally
Potentiometer Operation	Use 10k ohms for full range
Voltage Tolerance	+/- 48 V
Current Output	0.5 mA with 10k pot (for passive resistive controls)

RS-232 Port

Female DB9 connector (setup and diagnostics purposes only)

QSCControl Port

Neutrik Ethercon RJ45 ruggedized data connector

CobraNet Port

Neutrik Ethercon RJ45 ruggedized data connector

Indicators

QSCControl Status	Yellow Link, Tx, Rx, front panel / Green Link, Tx, Rx, rear panel
CobraNet Status	Yellow Link, Tx, Rx, front and rear panel
Power	Blue, front panel
Diagnostic	Red, front panel
DataPort Status (port)	Tri-state (red, green, yellow), front panel
LCD Data Display	2 line x 16 character, backlit, front panel

Specifications subject to change without notice.

1675 MacArthur Boulevard • Costa Mesa, CA 92626 • Ph: 800/854-4079 or 714/957-7100 • Fax: 714/754-6174

BASIS 904zz - 04/23/07