Normal CHLS4RGB



Incorrect connection CHLS4RGB





CAUTION

THIS BAG CONTAINS MOISTURE AND ELECTROSTATIC SENSITIVE DEVICES



- 1. 建議未拆封前儲存條件:5℃~30℃,最大相對濕度60%。
- 2. 袋子開封後,元件若將進行紅外線回銲、氧相回銲、或類似的銲接處理。必須
 - a. 24小時内完成銲接工作。
 - b. 儲存低於30%RH。
- 3. 假如不符合2a或2b的條件,則元件必須烘烤。
- 4. 若元件須烘烤,烘烤條件寫:60℃±3℃,12小時。

CAUTION:

1. Recommended storage condition:

At 5°C~30°C and relative humidity 60% RH max.

- 2. After this bag is opened, devices that will be applied to infrared reflow, vapor-phase ref or equivalent soldering process must be: Red wire= 12V
 - a. Completed within 24 hours.
 - b. Stored at less than 30% RH.
- Black wire = 0V (blue light output)
- Blue wire = 0V (green light outpu 3. Devices require baking before mounting, if green wire = 0V (red light output) 2a or 2b is not met
- 4. If baking is required, devices must be baked under below conditions: 12 hours at 60°C ± 3°C

Sealing date see bar code label. (封合日期請參考條碼標示)

Date and time opened (周封日期及時間)

Connection to <u>K8088</u>, <u>VM146</u>, <u>VM151</u>



